

NKL 8110C-OR - 500

NKL 8115C-OR - 305

U/UTP 10

, 0,50

, .5,

LSZH -40

✓ ISO/IEC 11801,  
EN 50173 TIA/EIA-568

✓

✓

100 /c.

NKL 811x -OR

10

5

(LSZH).

500 305



	NKL 811xC-OR	
	5	
	100	
	U/UTP	
	10	
	24 AWG (0,50 ± 0,01 )	
	(HDPE)	
	0,22 ± 0,02	
	0,9 ± 0,05	
	LSZH	
	(A)-HFLTx	
	/	
	0,85 ± 0,05	
	8,6 ± 0,3	
	85,0 ± 1,0 /	
	15-	
	10-	
	100	
	100 ± 15	
(NVP)	0,69 ± 0,1	
	95 /	
	305	500
	54429, ISO/IEC 11801, EN 50173 TIA/EIA-568	
	10BASE-T, 100BASE-TX, 100BASE-T4, 1000BASE-T, ATM-25, ATM-51, ATM-155, 100VG-AnyLan, TR-4, TR-16 Active, TR-16 Passive	
	-40 +70 °C.	0 +70 °C. -40 +70 °C
( , )	500x330	
	1	

								3
NKL 8110C-OR	5	10	UTP	/		305	-	-
NKL 8115C-OR	5	10	UTP	/		500	0,099825	45,000