

NMC-CA6SE2-924C-FT-FT-**xxx**

NIKOMAX,
KJ FT -
HF

6,

KJ FT,

, 6

()-



NMC-CA6UE2-924 -FT-FT-**xxx**

Keystone

NMC-CA6UE2-924 -FT-FT-**xxx**

6

6.

(A)-HF.

6

750-

«FT»

NIKOMAX



	NMC-CA6SE2-924C-FT-FT-xxx			
	-			
	6 x RJ45 - 6 x RJ45			
	xxx ()			
	-20 +60 °C.	0	+50 °C.	-20 +60 °C
	1			

	6
	250
	F/UTP
	4
	23 AWG (0,57 ± 0,01)
	26 AWG (0,40)
	0,25 ± 0,02
	1,12 ± 0,05
	0,55 ± 0,05
	7,4 ± 0,4
	(HDPE)
	()-HF
	(100%)
	1 - 250
	100 ± 15 0
(DC)	95 /
	50
(NVP)	0,67 ± 0,1
(500)	5000 M *
	1 /1
	1600 /
	56 /
	5%
	33
	45 /100
	54,8 ± 0,5 /
	10-
	8-
	100 H
	54429, ISO/IEC 11801, EN 50173, TIA/EIA-568
	10BASE-T, 100BASE-TX, 100BASE-T4, 1000BASE-T, 2.5GBASE-T, 5GBASE-T, ATM-25, ATM-51, ATM-155, 100VG-AnyLan, TR-4, TR-16 Active, TR-16 Passive
	-20 +60 °C. 0 +50 °C. -20 +60 °C

: xxx - (005 - 5 , 010 - 10 . .)

	6
	250
	RJ45/8P8C
	(50) (-100)
	750-
IDC ()	FT-TOOL/110/KRONE
	T568A/B
	-24-22 AWG (0,50-0,65)
IDC	
IDC	(100)
	-
	UL94V-0
	()
	17 19 40
	500 (100)
	1000 ,60 1
	20
IDC	2,5
	ISO/IEC 11801, EN 50173, TIA/EIA-568
	10BASE-T, 100BASE-TX, 100BASE-T4, 1000BASE-T, 2.5GBASE-T, 5GBASE-T, ATM-25, ATM-51, ATM-155, 100VG-AnyLan, TR-4, TR-16 Active, TR-16 Passive
	-40 +70 °C. -10 +60 °C

				3	
NMC-CA6SE2-924C-FT-FT-010	()-HF	-	10	-	-
NMC-CA6SE2-924C-FT-FT-030	()-HF	-	30	-	-
NMC-CA6SE2-924C-FT-FT-050	()-HF	-	50	-	-